



EASY WALL

In CMPC we are committed to provide high quality products and offer an excellent service. That is why we have been developing SELEX PLYWOOD; a stable and reliable Plywood panel with high quality and amazing appearance.

- Consistent top quality.
- Easy to work with.
- 100% Radiata pine.
- FSC[®] certified product.



The mark of
responsible forestry

Ask about our FSC® certified products.

PRODUCT BENEFITS AND APPLICATIONS FEATURES

-  Board intended for structural use in the construction area.
-  Each panel has an shiplap edge for quick installation, ensuring excellent bonding and finish.
-  Easy handling due to their low weight - volume ratio.
-  Test and test methods
 - Meet the requirements of impact resistance according to EN 12871 – for Wall sheathing on studs.
-  Applicable norms and regulations
 - EN 596 – Timber structures – Testing procedure; soft body impact test of timber frame walls.

MAIN APPLICATIONS

-  Walls

FEATURES

	 Selex C	 Selex D
Finishing		
Sanding grade	150	120
Natural defects		
Sound knots	Up to 40 mm. wide	Up to 65 mm. wide
Unsound knots	Up to 40 mm. wide	Up to 65 mm. wide
Knot holes	Up to 25 mm. wide	Up to 65 mm. wide
Pitch pockets	Allowed	Allowed
Bark pockets	Allowed	Allowed
Freckles	Allowed	Allowed
Machining defects		
Open cracks	Up to 25 mm. wide	Up to 25 mm. wide
Fungal stains	Allowed	Allowed
Roughness	Allowed	Allowed
Repairs		
Inner splits in knots	Not applicable	Not applicable
Routings with polyurethane	Not applicable	Not applicable
Putty patches	Not applicable	Not applicable

GENERAL SPECIFICATIONS

Dimensions: 2' x 8' (618 x 2400 mm) Net size: 600	Thickness (mm)	12	15
	N° of plies	5	5
Density	480 – 550 kg / m ³		
Adhesive	Formaldehyde emission meet E1 standard.		
Moisture Content	8% to 12 % for all boards.		
Forestry Certification	FSC® Certified product.		

